

**SC Board of Professional Engineers and Surveyors**  
**Policy regarding setting Control Monuments**  
**(Addendum to Board meeting minutes, March 11, 2008)**

Excerpt from Title 40, Chapter 22, Statutes governing the practice of engineers and surveyors

(24) 'Practice of TIER A surveying' means providing professional services including, but not limited to, consultation investigation, testimony evaluation, expert technical testimony, planning, mapping, assembling, and interpreting reliable scientific measurements and information relative to the location, size, shape, or physical features of the earth, the space above the earth, or part of the earth, and utilization and development of these facts and interpretation into an orderly survey map, site plan, report, description, or project. The practice of TIER A surveying consists of three separate disciplines: land surveying, photogrammetry, and geographic information systems. A surveyor may be licensed in one or more of the disciplines and practice is restricted to only the discipline or disciplines for which the land surveyor is licensed. The practice of TIER A surveying does not include the use of geographic information systems to create maps pursuant to Section 40-22-290, analyze data, or create reports. The scope of the individual disciplines are identified as follows:

(a) Land surveyor:

(1) locates, relocates, establishes, reestablishes, lays out, or retraces any property line or boundary of any tract of land or any road, right-of-way, easement, alignment, or elevation of any fixed works embraced within the practice of land surveying, or makes any survey for the subdivision of land;

(2) determines, by the use of principles of land surveying, the position for any survey monument or reference point; or sets, resets, or replaces such monument or reference; determines the topographic configuration or contour of the earth's surface with terrestrial measurements; conducts hydrographic surveys;

(3) conducts geodetic surveying which includes surveying for determination of geographic position in an international three-dimensional coordinate system, where the curvature of the earth must be taken into account when determining directions and distances; geodetic surveying includes the use of terrestrial measurements of angles and distances, as well as measured ranges to artificial satellites.

(b) A photogrammetric surveyor determines the configuration or contour of the earth's surface or the position of fixed objects on the earth's surface by applying the principles of mathematics on remotely sensed data, such as photogrammetry.

(c) A geographic information systems surveyor creates, prepares, or modifies electronic or computerized data including land information systems and geographic information systems relative to the performance of the activities described in subitems (a) and (b).

**(d) An individual licensed only as a geodetic surveyor before July 1, 2004, determines the geographic position in an international three-dimensional coordinate system, where the curvature of the earth must be taken into account when determining directions and distances; geodetic surveying includes the use of terrestrial measurements of angles and distances, as well as measured ranges to artificial satellites. A geodetic surveyor is not authorized to perform the other services a land boundary surveyor is authorized to perform. [bolding added]**

**Interpretation of  
Section 40-22-20(24)(d)**

It is the interpretation of the South Carolina Board of Professional Engineers and Surveyors (the Board) that the language in Section 40-22-20(24)(d) stating, in part, that a geodetic surveyor “determines the geographic position in an international three-dimensional coordinate system, where the curvature of the earth must be taken into account when determining directions and distances; geodetic surveying includes the use of terrestrial measurements of angles and distances, as well as measured ranges to artificial satellites” means that geodetic surveyors may determine or set control monuments. In this interpretation, a “control monument” is further defined as a Geodetic Control Monument where the geographic coordinates have been determined by a geodetic surveyor or a land boundary surveyor. Determining or setting control monuments is considered within the practice of geodetic surveying or land boundary surveying.

Adopted by the Board in principal February 12, 2008

Final language adopted by Board March 11, 2008

G:\POLICIES\Policy on Control Monuments.doc